






















## PLUMBING FIXTURE SCHEDULE

12. NOTICE THE FOLLOWING TYPES OF TRAPS ARE PROHIBITED: 1) TRAPS THAT DEPEND ON MOVING PARTS TO MAINTAIN THE SEAL; 2) BELL TRAPS; 3) WATER WILTED TRAPS; 4) TRAPS NOT INTEGRAL WITH A FIXTURE AND THAT DEPEND ON INTERIOR PARTITIONS FOR THE SEAL, EXCEPT THOSE TRAPS CONSTRUCTED OF AN APPROVED MATERIAL THAT IS RESISTANT TO CORROSION AND DEGRADATION. TRAP GUARD AS MANUFACTURED BY PRO-SET SYSTEMS OR SIMILAR PRODUCTS ARE NOT CURRENTLY APPROVED.

13. INSTALL WATER HEATERS PER CH 5 OF THE 2008 IAPMO UNIFORM PLUMBING CODE. A FULL-OPEN VALVE IS REQUIRED ON THE WATER SUPPLY PIPE TO EVERY WATER HEATER. AN

SYMBOL	FIXTURE	DESCRIPTION					
		W	V	CW	HW	T	
 171	HANDICAP WATER CLOSET	4"	2"	1-1/2"	-	INT	"SLOAN" MODEL ST-2029-A UNIVERSAL WATER CLOSET. ADA APPROVED, "SLOAN" MODEL 8111 ELECTRONIC DUAL FLUSH VALVE (1.1/1.6 GPF) ADA COMPLIANT, "OLSONITE" MODEL 10CT OPEN FRONT SEAT.
 188	WATER CLOSET	4"	2"	1-1/2"	-	INT	"SLOAN" MODEL ST-2050-A UNIVERSAL WATER CLOSET, "SLOAN" MODEL 8111 ELECTRONIC DUAL FLUSH VALVE (1.1/1.6 GPF) ADA COMPLIANT, "OLSONITE" MODEL 10CT OPEN FRONT SEAT.
 172	WALL HUNG HANDICAPPED URINAL	2"	1-1/2"	3/4"	-	-	"SLOAN" MODEL SU-1009-A, "SLOAN" MODEL 8186-1.0 LOW CONSUMPTION (1.0 GPF), MOUNT PER ADA GUIDELINES.
 173  174	LAVATORY	2"	1-1/2"	1/2"	1/2"	2"	"JUST" #JUF-A-ADA-1521-A-18GA, UNDERMOUNT, FAUCET "SLOAN" MODEL EBF-650 WITH MOTION SENSOR, SUPPLIES, & P-TRAP, 0.5 GPM, ADA COMPLIANT.
 175	FLOOR SINK	3"	2"	-	-	3"	"J.R. SMITH" #3100
 176	FLOOR DRAIN	2"	1-1/2"	-	-	2"	"J.R. SMITH" #2005Y-(A) W/TRAP PRIMER
 177	TRAP PRIMER	-	-	1/2"	-	-	PRECISION PLUMBING PRODUCTS P-2 (PRESSURE ACTUATED) - LOCATE IN WALL MOUNTED ACCESSIBLE BOX W/ COVER @ 24" A.F.F.
 178	HOSE BIBB	-	-	3/4"	-	-	MIFAB #MHY-206-K (INTEGRAL WITH VACUUM BREAKER) ENCASED TYPE NON-FREEZE
 179	RECIRC. PUMP	-	-	-	-	-	TACO 007 BRONZE CONSTRUCTION; 1" CONNECTION; NON METALLIC IMPELLER, ELECTRICAL CHARACTERISTICS: 115V/60/1, 1/25 HP @ 3250 RPM
 180	BACKFLOW PREVENTER	-	-	2"	-	-	"WATTS" # 909M1-GT OR EQUAL, REDUCED PRESSURE PRINCIPLE BACKFLOW - PROVIDE WITH AIR GAP FITTING AND DRAIN LINE QUATER TURN BALL VALVES AND STRAINER
 181	BACKFLOW PREVENTER	-	-	1/2"	-	-	DOUBLE CHECK BACKFLOW PREVENTION DEVICE, "WATTS" #007GT.
 182	BACKFLOW PREVENTER	-	-	1/2"	-	-	REDUCED PRESSURE BACKFLOW PREVENTION DEVICE, "WATTS" #SS009OT. PROVIDE WITH AIR GAP FITTING AND DRAIN LINE TO NEAREST FLOOR SINK. (TYPICAL)
 183	GREASE TRAP	2"	-	-	-	-	WADE MODEL 5150 GREASE INTERCEPTOR, 24 GPM, 50 LBS OF GREASE MAX CAPACITY, REFER TO P1/P11-CS.
 184	HAND SINK	2"	1-1/2"	1/2"	1/2"	2"	CABINET MANUFACTURER PROVIDED SINK AMERICAN STANDARD FAUCET MODEL #4205.280, LOOP HANDLE, HI-FLOW SPOUT AND METAL LOOP HANDLE, 0.5 GPM
 185	HAND SINK	2"	1-1/2"	-	-	2"	CABINET MANUFACTURER PROVIDED SINK
 186	HAND SINK FAUCET (MOTION SENSOR)	-	-	1/2"	1/2"	-	HAND SINK PROVIDED BY CABINET MANUFACTURER, FAUCET - "SLOAN" MODEL EBF-650 WITH MOTION SENSOR, SUPPLIES, & P-TRAP, 0.5 GPM, ADA COMPLIANT
 187	DRINK DISPENSER	-	-	1/2"	-	-	SEE SHEET A7 FOR ADDITIONAL INFORMATION.
 188	ICE MAKER	-	-	1/2"	-	-	SEE SHEET A7 FOR ADDITIONAL INFORMATION.
 189	FROZEN BEVERAGE DISPENSER	-	-	1/2"	-	-	SEE SHEET A7 FOR ADDITIONAL INFORMATION.
 190	COFFEE BREWER	-	-	1/2"	-	-	SEE SHEET A7 FOR ADDITIONAL INFORMATION.
191	CAPPUCINO MAKER	-	-	1/2"	-	-	SEE SHEET A7 FOR ADDITIONAL INFORMATION.
129	3-COMP SINK	2"	1-1/2"	-	-	IND.	"SUPERIOR PRODUCTS", 14 IN. DEEP SCULLERY SINK 90 IN. L, 2-18 IN. DRAINBOARDS, 3 TUBS (18 IN. X 18 IN.), ITEM #81253;
129a	WALL-MOUNTED 3-COMP SINK FAUCET	-	-	3/4"	3/4"	-	FAUCET WALL MOUNTED FAUCET BASED ONLY W/ 8 IN. CENTERS, SUPERIOR PRODUCTS ITEM #804093; FAUCET SWNG NOZZLE ONLY 12 IN. ITEM #809552.
130	WATER FILTER	-	-	3/4"	-	-	ARS 9437-10
133	HAND SINK	IND.	2"	1/2"	1/2"	IND.	LAMBERTSON LBS-1906-11-1 1 1/2"W X 16 1/2"L X 7" DEEP HAND SINK JS-47-TGSA, FAUCET, J-35 ADA DRAIN SYSTEM AND VACUUM BREAKER, 0.5 GPM
143	MOP SINK	3"	2"	3/4"	3/4"	2"	"FIAT" #MSD 2424 W/ #830-AA, #832-AA AND #1453-BB. PROVIDE FAUCET WITH VACUUM BREAKER
145	WATER HEATER	-	-	1-1/4"	1-1/4"	-	AO SMITH DEN-52, 50 GAL. STORAGE, ELECTRICAL CHARACTERISTICS: 4.5 KW, 208V, 1PH, OPR. WEIGHT: 131 LBS. DIMENSION: 55"x21"x18"
GH	GROUND HYDRANT	-	-	3/4"	-	-	MIFAB #MHY-601 (INTEGRAL WITH VACUUM BREAKER) SELF-DRAINING GROUND HYDRANT 1' BURY DEPTH WITH BRONZE LOCK COVER

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	SOIL WASTE LINE (W)		SHUT OFF VALVE (GATE)
	VENT LINE (V)		CHECK VALVE
	COLD WATER (C.W.)		UNION
	HOT WATER (H.W.)		LUBRICATED PLUG VALVE
	HOT WATER RETURN		HOSE BIBB (H.B.)
	TEMPERED WATER		BRANCH RISE OFF MAIN
	DRAIN LINE		SURFACE CLEANOUT
	BUILDING SEWER		FLOOR CLEANOUT
	FLOOR DRAIN (F.D.)		GLOBE VALVE
	FLOOR SINK (F.S.)		BALL VALVE
	ROOF DRAIN (R.D.)		ROOF DRAIN LEADER
	OVER FLOW DRAIN		OVERFLOW DRAIN LEADER
	WALL CLEANOUT		CONDENSATE DRAIN LINE
	POINT OF CONNECTION		INDUSTRIAL COLD WATER

NOTE: ONLY THOSE SYMBOLS SHOWN ON THE DRAWING APPLY

